



## HANGING INSTRUCTIONS FOR JEWELS

### Prior to Installation

- Examine each roll to be sure the product is what was ordered. Each bolt should be rolled out so color and shading can be examined to your satisfaction. All rolls must have the same production number. Hang in sequence as cut from bolt. No adjustment or claim will be considered because of variation in color or shading once material has been cut.
- Carefully Inspect the Installation after applying three strips before proceeding. If, at any time during the installation, a discrepancy occurs, stop . Contact your Supplier or PRIME Wallcoverings before proceeding.
- Avoid folding or creasing which may create markings on the product.
- Material should be hung w/the same top-not reversed.
- Material is not pre-trimmed.

### Wall Preparation

- Proper Wall preparation is essential, Generally, they must be smooth and clean, Wallcoverings will not adhere to dirt, soap or grease. Clean the walls with house hold detergent or ammonia and rinse with clean water.
- Remove all old wallcoverings, clean wall, Always apply Wallcovering primer prior to installation. This ensures an even surface for the wallcovering to adhere making it easier to hang and remove later on.
- If working around switchplates turn off electricity.
- Remove any loose or flaking paint and fill cracks with patching compound.
- Sand to a smooth finish. Sand off a bumps
- Apply a single coat of pigmented sealer on new and un painted walls. Followed by wallcovering primer/sizing.

### Important notes for application

- Trim JEWELS on the table, not on the wall
- Trim only from the back and double score ( This material cannot be double cut on the beaded face)
- Apply professional grade pre-mixed clear vinyl adhesive
- Use a new blade after each cut
- Use a new bristle brush after trimming with a single edge razor blade
- Wipe off excess paste from the face of the material with a soft moist cloth
- A wooden seam roller is recommended for the seams.

**The non-woven backing for JEWELS is highly flexible and can be installed on both inside and outside corners  
In situations where there is a light corner or surface that is not square create a template**

*Please contact*

**Our Customer Service Department if you have any further questions**