PRIME
WALL COVERINGS

Ulf Moritz Hanging Instructions

General note: Please inspect merchandise for damages before and after hanging the first 3 lengths. To avoid shading or color variation, use same lot number for all rolls. Save instruction label and sample cutting for possible product defects. Labor claims will not be honored. Under no circumstances will the hanging cost of more than three lengths be covered by the manufacturer.

The Ulf Moritz wallpaper is manufacture-technical produced and show material or handcrafted effects, which are intended from the designer. Irregularities at the wallpaper-surface are no reason for complaint.

Surface: Walls should be dry, clean, firm, solid, plain, neutral and bright in color. For very absorbent surfaces apply a primer, diluted if necessary to create a porous surface (e.g. DEXTRA PT, PUFAS Tapetengrund white)

Adhesive: We recommend special paste in the proportion 1:20 (1 package of 200 g diluted with 4 l of water). We recommend the addition of 10% to 15% dispersion glue for walls which are non-absorbing or poorly absorbing.

Pasting: Apply adhesive evenly onto surface with brush or roller. Measured strip of wallcovering is to be applied directly onto pasted surface and positioned into desired place. A roller may be used to flatten any air pocket or loose seams. Pasting machine may also be used. Pasted stripes may be applied immediately without booking (soaking) paper. Use a sharp knife to trim over-lapping along ceilings, windows and ledges. Subsequent strips should be butted along seams and evened with roller if necessary. Inside and outside corners should be overlapped by 8-10 cm (3-4 in.). Following strips should overlap by 4-6 cm (1-2 in.) and double cut with sharp razor knife. Loose strip is to be discarded and additional paste may be applied along edges if necessary. Avoid paste on the surface of the wallcovering. Any paste marks should immediately be removed with a sponge and clean water gently dabbing the area.

Redecorating: For easy stripping start at the top or bottom of the lengths, using a spatula to detach the edge, and peel off the strip in on continuous steady movement.